

Suzuki Samurai Adjustable/Removable Door Strap Kit (SKU# SIB-ADS)

Installation Instructions



CAUTION: Safety glasses should be worn at all times when working with vehicles and related tools and equipment.



Suggested Tools:

- Phillips Screwdriver
- Allen wrench: 3 mm (Supplied)

FOR ADDITIONAL COPIES OF THESE AND OTHER INSTRUCTIONS GO TO:

www.lowrangeoffroad.com and click on the "INSTRUCTIONS" tab.



Step 1

Open the passenger side door.



Step 2

Remove the (2) screws from the kick panel side of the door strap using a phillips screwdriver.



Step 3

Remove the (2) screws from the door side of the door strap using a phillips screwdriver.



Step 4

Remove the door strap and set it aside.





Step 5

Position one of the supplied door strap brackets to the door using the supplied allen head screws.

Note: Be sure to orient the smaller side of the bracket toward the other bracket and facing upward as shown in step 6.



Step 6

Tighten the allen screws using the tool provided.

Note: Do not over-tighten.



Step 7

Install the other supplied door strap bracket to the kick panel as shown.

Note: Be sure to orient the smaller side of the bracket toward the other bracket and facing upward as shown in step 8.



Step 8

Tighten the allen screws.





Step 9

Install the nylon web door strap as shown. We recommend installing the strap such that the excess, if there is any, be oriented under the dash as shown.

Note: The strap can be installed in several positions allowing the door to stop in a variety of open positions.



Step 10

Repeat Steps 1 through 9 on the driver side door.



Congratulations:

You have successfully completed a Samurai door strap. We hope these instructions have been helpful. If you have suggestions on how we can improve these instructions or our products email us at sales@lowrangeoffroad.com or call us at 801-805-6644.

As always, If you experience any difficulty during the installation of this product please contact Low Range Off-Road Technical Support at 801-805-6644 M-F 7:30am-5:30pm MST. Thank you for purchasing from Low Range Off-Road.



These instructions are designed as a general installation guide. Installation of many Low Range Off-Road products require specialized skills such as metal fabrication, welding and mechanical trouble shooting. If you have any questions or are unsure about how to proceed, please contact our shop at 801-805-6644 or seek help from a competent fabricator. Using fabrication tools such as welders, torches and grinders can cause serious bodily harm and death. Please operate equipment carefully and observe proper safety procedures.

Rock crawling and off-road driving are inherently dangerous activities. Some modifications will adversely affect the on-road handling characteristics of your vehicle. All products sold by Low Range Off-Road are sold for off road use only. Any other use or application is the responsibility of the purchaser and/or user. Some modifications and installation of certain aftermarket parts may under certain circumstances void your original dealer warranty. Modification of your vehicle may create dangerous conditions, which could cause roll-overs resulting in serious bodily injury or death. Buyers and users of these products hereby expressly assume all risks associated with any such modifications and use.

Revised 12/04/13© Copyright 2013 Low Range Off-Road, LC All Rights Reserved